



ELECTRIC STORAGE WATER HEATERS WITH DRY TUBULAR HEATING ELEMENTS										
CHARACTERISTICS										
Model	...	WV03039D	WV05039D	WV08039D	WV08046D	WV10046D	WV12046D	72280MD	72280D	72281D
Volume range	L	30	50	80	80	100	120	150	150	200
Energy efficiency class	...	C	C	C	C	C	C	C	C	C
Annual electricity consumption	kWh/annum	547	1403	1317	1327	1345	2623	2495	2495	2118
Rated pressure	MPa	0,8	0,8	0,8	0,8	0,8	0,8	0,8	0,8	0,8
Rated voltage	V~	230	230	230	230	230	230	230	230	230
Rated electrical power	kW	2x0,8	2x0,8	2x1,0	2x1,0	2x1,0	2x1,0	2x1,2	2x1,2	2x1,2
Thermostat temperature presetting	°C	75	75	75	75	75	75	75	75	75
Mixed water at 40 °C	L	-	96	142	141	181	238	283	283	391
Net weight	kg	14.2	18.5	26.5	24.5	29.2	33.5	40.5	46.5	57
CONNECTIONS										
1: Hot water outlet		G1/2 M	G1/2 M	G1/2 M	G1/2 M	G1/2 M	G1/2 M	G1/2 M	G1/2 M	G1/2 M
2: Cold water inlet - Drain		G1/2 M	G1/2 M	G1/2 M	G1/2 M	G1/2 M	G1/2 M	G1/2 M	G1/2 M	G1/2 M
3: Temperature indicator		•	•	•	•	•	•	•	•	•
4: External thermostat		•	•	•	•	•	•	•	•	•
5: Flange with heating elements		•	•	•	•	•	•	•	•	•
6: Illuminated switch		•	•	•	•	•	•	•	•	•
DIMENSIONS										
A	mm	560	760	1125	835	1005	1170	1415	1015	1255
C	mm	155	155	155	185	185	185	175	190	190
D	mm	387	387	387	462	462	462	460	586	586
E	mm	80	80	80	96	96	96	96	105	105
F	mm	410	410	410	484	484	484	474	600	600
G	mm	33	33	33	33	33	33	32	43	43

D - water heater with two dry tubular electric heating elements