



WATER HEATERS "EUREKA" FOR VERTICAL MOUNTING ON THE WALL										
CHARACTERISTICS										
Model	...	72269D	72267D	72268D	72265D	72270D	72266D	72280MD	72280D	72281D
Rated volume	L	30	50	80	80	100	120	150	150	200
Rated pressure	MPa	0,8	0,8	0,8	0,8	0,8	0,8	0,8	0,8	0,8
Rated voltage	V~	230	230	230	230	230	230	230	230	230
Rated electrical power	kW	2x0,8	2x0,8	2x1,0; 2x1,2	2x1,0	2x1,0	2x1,0	2x1,2	2x1,2	2x1,2
Warm-up time from 12-75 °C	h	1,4	2,34	3; 2,5	3	3,74	4,5	4,67	4,67	6,2
MIX 37 °C (temperature of the water in the water tank: 75 °C; water temperature of supply water: 12 °C)	L	76	126	195	195	250	297	378	378	494
Weight when empty	kg	13.5	18	24.5	24	29	32.5	40	44	49
CONNECTIONS										
1: Hot water outlet		G1/2 M	G1/2 M	G1/2 M	G1/2 M	G1/2 M	G1/2 M	G1/2 M	G1/2 M	G1/2 M
2: Cold water inlet - Drain		G1/2 M	G1/2 M	G1/2 M	G1/2 M	G1/2 M	G1/2 M	G1/2 M	G1/2 M	G1/2 M
3: Temperature indicator		-	-	-	-	-	-	-	-	-
4: Control panel		-	-	-	-	-	-	-	-	-
5: Flange with heating element		-	-	-	-	-	-	-	-	-
DIMENSIONS										
A	mm	555	750	1065	825	1000	1165	1415	1015	1255
B	mm	470	665	980	740	915	1080	1330	930	1170
C	mm	145	145	145	175	175	175	175	190	190
D	mm	385	385	385	460	460	460	460	586	586
E	mm	80	80	80	96	96	96	96	105	105
F	mm	400	400	400	474	474	474	474	600	600
G	mm	32	32	32	32	32	32	32	43	43
M	mm	-	-	-	-	-	-	1003	560	780