



ELECTRIC STORAGE WATER HEATERS FOR WALL MOUNTING										
CHARACTERISTICS										
Model	...	72269	72267	72268	72265	72270	72266	72280M	72280	72281
Volume range	L	30	50	80	80	100	120	150	150	200
Energy efficiency class		C	C	C	C	C	C	C	C	C
Annual electricity consumption	kWh	532	1323	1324	1340	1400	1425	2553	2517	2607
Rated pressure	MPa	0,8	0,8	0,8	0,8	0,8	0,8	0,8	0,8	0,8
Rated voltage	V~	230	230	230	230	230	230	230	230	230
Rated power	kW	1,5; 2,0; 3,0	1,5; 2,0; 3,0	1,5; 2,0; 3,0	1,5; 2,0; 3,0	1,5; 2,0; 3,0	1,5; 2,0; 3,0	2,0; 3,0	2,0; 3,0	2,0; 3,0
MIX 40 °C at temperature of the water inside the water tank 75 °C and temperature of the water from the water mains 10-12 °C)	L	-	71	121	120	152	170	229	226	292
Net weight	kg	13.5	18	24.5	24	29	32.5	40	44	49
CONNECTIONS										
1: Hot water outlet		G1/2 M	G1/2 M	G1/2 M	G1/2 M	G1/2 M	G1/2 M	G1/2 M	G1/2 M	G1/2 M
2: Cold water inlet - Drain		G1/2 M	G1/2 M	G1/2 M	G1/2 M	G1/2 M	G1/2 M	G1/2 M	G1/2 M	G1/2 M
3: Temperature indicator		-	-	-	-	-	-	-	-	-
4: Control panel		-	-	-	-	-	-	-	-	-
5: Flange with a heating element		-	-	-	-	-	-	-	-	-
DIMENSIONS										
A	mm	555	750	1115	825	1000	1165	1415	1015	1255
B	mm	470	665	1030	740	915	1080	1330	930	1170
C	mm	145	145	145	175	175	175	175	190	190
D	mm	385	385	385	460	460	460	460	586	586
E	mm	80	80	80	96	96	96	96	105	105
F	mm	400	400	400	474	474	474	474	600	600
G	mm	32	32	32	32	32	32	32	43	43
M	mm	-	-	-	-	-	-	1003	560	780