



HOT WATER STORAGE TANKS, FOR INSTALLATION ON THE FLOOR

TECHNICAL DATA

Model	...	FV15060	FV20060	FV30067
Volume group	...	150	200	300
Energy efficiency class	...	C	C	C
Annual electricity consumption	kWh/annum	2339	2375	4159
Mixed water at 40°C	L	268	372	469
Rated pressure	MPa	0.8	0.8	0.8
Insulation thickness	mm	75	75	85
Gross weight	kg	52	58	75

ELECTRICAL PART

Rated voltage	V	0 / 230~	0 / 230~	0 / 230~ / 400 3N~
Rated electrical power	kW	0 / 3	0 / 3	0 / 3 / 6 / 9
Maximum temperature in the tank of heated with electric resistance heater	°C	75	75	75

CONNECTIONS

1: Thermometer		Да	Да	Да
7: Flange with a heating element		Да	Да	Да
9: Fresh water inlet - Drain		G3/4 F	G3/4 F	G3/4 F
10: Recirculation		G3/4 F	G3/4 F	G3/4 F
11: Hot water outlet		G3/4 F	G3/4 F	G3/4 F
12: Hot water outlet		G3/4 F	G3/4 F	G3/4 F

DIMENSION

A	mm	210	210	210
C	mm	660	855	840
D	mm	600	600	670
G	mm	75	75	85
H	mm	1150	1430	1605
M	mm	690	690	760
P	mm	890	1155	1315