



NON-ENAMELED BUFFER TANKS WITH TWO BLACK HEAT EXCHANGERS

TECHNICAL DATA					
Model	...	BCS2 750F	BCS2 1000F	BCS2 1500F	BCS2 2000F
Volume group	...	750	1000	1500	2000
Energy efficiency class	...	-	-	-	-
Standing loss	W	127	137	161	186
Rated pressure	MPa	0.3	0.3	0.3	0.3
Volume	L	721	920	1455	1978
Insulation thickness	mm	80	80	100	100
Gross weight	kg	195	230	342	414
HEAT EXCHANGERS					
Surface area S1	m ²	2.03	3.04	3.04	4.25
Volume S1	L	13.34	19.95	19.95	27.94
Pressure loss S1	mbar	50	70	70	80
Surface area S2	m ²	1.22	2.03	2.03	2.73
Volume S2	L	7.99	13.34	13.34	17.97
Pressure loss S2	mbar	20	40	30	50
CONNECTIONS					
1: Inlet / Outlet		G2 F	G2 F	G2 F	G2 F
2: S1		G1 F	G1 F	G1 F	G1 F
3: S2		G1 F	G1 F	G1 F	G1 F
5: Socket for thermostat		G1/2 F	G1/2 F	G1/2 F	G1/2 F
6: Additional socket		G1 1/2 F	G1 1/2 F	G1 1/2 F	G1 1/2 F
7: Inlet / Outlet		G1 1/4 F	G1 1/4 F	G2 F	G2 F
DIMENSIONS					
A	mm	330	330	385	395
B	mm	360	360	425	435
C	mm	890	1045	1220	1230
D	mm	1010	1010	1250	1400
E	mm	940	1100	1245	1255
F	mm	645	755	845	855
G	mm	80	80	100	100
H	mm	1665	2000	2210	2255
I	mm	470	630	730	730
J	mm	290	470	470	470
K	mm	960	1185	1305	1315
L	mm	1270	1610	1765	1775