



NON-ENAMELED BUFFER TANKS WITH ONE BLACK AND ONE STAINLESS STEEL HEAT EXCHANGER

TECHNICAL DATA

Model	...	BCWS 300K	BCWS 500K80
Volume group	...	300	500
Energy efficiency class	...	B	B
Standing loss heat	W	51	72
Rated pressure	MPa	0.3	0.3
Volume	L	247	443
Insulation thickness	mm	85	80
Gross weight	kg	75	146
HEAT EXCHANGERS			
Surface area S1	m ²	1.12	1.85
Volume S1	L	5.44	12.15
Pressure loss S1	mbar	50	40
Surface area heat exchanger DHW	m ²	3.03	4.65
Volume heat exchanger DHW	L	16.64	25.72

CONNECTIONS

1: Inlet / Outlet		G1 1/2 F	G2 F
2: S1		G3/4 F	G1 F
4: Heat exchanger DHW		G1 F	G1 F
5: Socket for thermostat		G1/2 F	G1/2 F
6: Additional socket		G1 1/2 F	G1 1/2 F
7: Inlet / Outlet		G3/4 F	G1 1/4 F

DIMENSIONS

A	mm	205	220
B	mm	235	260
C	mm	835	960
D	mm	670	800
F	mm	575	635
G	mm	85	80
H	mm	1595	1765
I	mm	530	630
K	mm	945	1045
L	mm	1315	1460