



**NON-ENAMELED BUFFER TANKS WITH STAINLESS STEEL HEAT EXCHANGER**

**TECHNICAL DATA**

Model	...	BCW 750F	BCW 1000F	BCW 1500F	BCW 2000F
Volume group	...	750	1000	1500	2000
Energy efficiency class	...	-	-	-	-
Standing loss heat	W	125	136	159	183
Rated pressure	MPa	0.3	0.3	0.3	0.3
Volume	L	698	931	1444	1956
Insulation thickness	mm	80	80	100	100
Gross weight	kg	208	218	313	373

**HEAT EXCHANGER**

Surface area heat exchanger DHW	m <sup>2</sup>	5.16	7.50	9.00	11.24
Volume heat exchanger DHW	L	28.52	41.61	49.93	62.41

**CONNECTIONS**

1: Inlet / Outlet		G2 F	G2 F	G2 F	G2 F
4: Heat-exchanger for DHW		G1 F	G1 F	G1 F	G1 F
5: Socket for thermostat		G1/2 F	G1/2 F	G1/2 F	G1/2 F
6: Additional socket		G1 1/2 F	G1 1/2 F	G1 1/2 F	G1 1/2 F
7: Inlet / Outlet		G1 1/4 F	G1 1/4 F	G2 F	G2 F

**DIMENSIONS**

A	mm	330	330	385	395
C	mm	890	1045	1220	1230
D	mm	1010	1010	1250	1400
F	mm	645	755	845	855
G	mm	80	80	100	100
H	mm	1665	2000	2210	2255
K	mm	960	1185	1305	1315
L	mm	1270	1610	1765	1775