



WATER HEATERS WITH HEAT EXCHANGER FOR HORIZONTAL WALL MOUNTING

CHARACTERISTICS					
Model	...	WH08039LSL; WH08039RSR	WH08046LSL; WH08046RSR	WH10046LSL; WH10046RSR	WH12046LSL; WH12046RSR
Volume range	L	80	80	100	120
Energy efficiency class		C	C	C	C
Rated pressure	MPa	0.7	0.7	0.7	0.7
Rated voltage	V~	230	230	230	230
Rated electrical power	W	2 (3)	2 (3)	2 (3)	2 (3)
Heat exchanger surface area	m ²	0.36	0.35	0.35	0.59
Heat exchanger inside volume	L	1.31	1.71	1.71	2.85
Thermal power heat exchanger according EN 12897 (15-60°C; 15 l/min; 80°C)	kW	5.2	7	6.5	9
Warm-up time from 15-60 °C with heat exchanger (15 l/min; 80°C) (EN 12897)	min	25	23	30	27
Pressure drop across the coil	mbar	30	50	50	60
Standing loss	W	62	63	67	71
Weight	kg	32	29	33.5	39
CONNECTIONS					
1: Hot water outlet		G1/2 F	G1/2 F	G1/2 F	G1/2 F
2: Cold water inlet - Drain		G1/2 F	G1/2 F	G1/2 F	G1/2 F
3: Temperature indicator		-	-	-	-
4: Control panel		-	-	-	-
5: Flange with a heating element		-	-	-	-
6: Heating coil - Feed		G1/2 M	G1/2 M	G1/2 M	G1/2 M
7: Heating coil - Return		G1/2 M	G1/2 M	G1/2 M	G1/2 M
8: Illuminated switch		-	-	-	-
DIMENSIONS					
A	mm	1125	835	1005	1170
B	mm	617	262	434	600
C	mm	155	185	185	185
D	mm	387	462	462	462
E	mm	80	96	96	96
F	mm	410	484	484	484
G	mm	33	33	32	33
K	mm	223	250	250	250
M	mm	770	415	587	753

R - all positions are on the right side