



BUFFER TANK FOR VERTICAL AND HORIZONTAL MOUNTING

TECHNICAL DATA

Model	...	BCE 60(R)	BCE 80(R)	BCE 120(R)
Volume range	...	60	80	120
Energy efficiency class	...	C	C	C
Standing loss heat	W	56	60	68
Rated pressure	MPa	0.6	0.6	0.6
Capacity	L	64	75	116
Working temperature min/max	°C	5 / 95	5 / 95	5 / 95
Insulation thickness	mm	33	33	33
Gross weight	kg	29	31.5	42

CONNECTIONS

	G1 1/4F	G1 1/4F	G1 1/4 F
1: Inlet / outlet	G1 1/4F	G1 1/4F	G1 1/4 F
2: Flange	Yes	Yes	Yes
3: Ball valve	G1/2	G1/2	G1/2
4: Socket for thermostat	G1/2 F	G1/2 F	G1/2 F
5: Additional socket	G1 1/2 F	G1 1/2 F	G1 1/2 F

DIMENSIONS

	mm	715	810	1150
H	mm	280	375	715
J	mm	320	415	755
M				

Designations and Installation Positions:

BCE - Enameled water tank.

BCE xxx - Installation Positions: Vertical on the floor - outlets on the top and on the left. Horizontal on the wall - outlets on the left and on the bottom.

BCE xxxR - Installation Positions: Vertical on the floor - outlets on the top and on the right. Horizontal on the wall - outlets on the right and on the bottom.