



NON-ENAMELED BUFFER TANKS WITH STAINLESS STEEL HEAT EXCHANGER

TECHNICAL DATA

Model	...	BCW 750F	BCW 1000F	BCW 1500F	BCW 2000F
Volume group	...	750	1000	1500	2000
Rated pressure	MPa	0.3	0.3	0.3	0.3
Volume	L	698	931	1444	1956
Insulation thickness	mm	80	80	100	100
Gross weight	kg	167	181	313	373

HEAT EXCHANGER

Surface area heat exchanger DHW	m ²	5.16	7.50	9.00	11.24
Volume heat exchanger DHW	L	28.52	41.61	49.93	62.41

CONNECTIONS

1: Inlet / Outlet		G2 F	G2 F	G2 F	G2 F
4: Heat-exchanger for DHW		G1 F	G1 F	G1 F	G1 F
5: Socket for thermostat		G1/2 F	G1/2 F	G1/2 F	G1/2 F
6: Additional socket		G1 1/2 F	G1 1/2 F	G1 1/2 F	G1 1/2 F
7: Inlet / Outlet		G1 1/4 F	G1 1/4 F	G2 F	G2 F

DIMENSIONS

A	mm	330	330	385	395
C	mm	890	1045	1220	1230
D	mm	1010	1010	1250	1400
F	mm	645	755	845	855
G	mm	80	80	100	100
H	mm	1665	2000	2210	2255
K	mm	960	1185	1305	1315
L	mm	1270	1610	1765	1775