





Series:

Eureka


Warranty:

3 years full warranty

Technologies:



IP24



SOLUTION FOR HART AND SOFT WATER

- Two dry tube heaters – the heating element does not go into a direct contact with water; it is tightly fitted inside a thin tube which is enameled together with the water tank flange. The lack of calcareous precipitations on heater and water tank whole inside surface maintains the energy efficiency of water heater and extends its life-time;
- ENERGY SAVING - the thick insulation of 35 mm CFC-free polyurethane foam ensures extremely low heat losses and saves money;
- LONG LIFE – water tank coated with wear-proof zirconium enamel and two magnesium protectors for an optimal corrosion protection of the whole volume;
- RELIABLE – with a reliable "6-level protection"
- EASY MAINTENANCE - if necessary, the dry heater can be replaced without having to drain out the water from the water heater;
- External thermostat – for setting the water heating temperature;
- Temperature indicator – to read the water heating temperature;
- Combined safety valve – jointly acting as balance and non-reverse and differential valve;
- Specific oval flange – of a special construction to guarantee your safety;
- Luminous double switch;
- Optionally, it is possible to fit an anode tester to control the corrosion protection state.

Installation:	Vertical
Capacity range:	120
Water tank:	Enameled
Nominal power (kW):	2
Energy efficiency class:	C
Control:	mechanical control
Type of electric heating element:	Dry heating element
Weight [kg]:	31.5
Dimensions ØxH [mm]:	462 x 1170
Voltage [V]:	230 V~
Nominal pressure [MPa]:	0.7
IP protection:	IP24
Load profile:	M
Colors:	White