







### Technologies:



ENERGY SAVING, RELIABLE, LONG LIFE

- ENERGY SAVING

- With a lower positioned heat exchanger to accumulate to the maximum the alternative energy sources. This model is suitable to connect to solar collectors, boiler or heat pump system. The heat exchanger larger area allows for the universal usage of this model of water heaters;

- Sensor sockets to heat exchanger - the mounted thermal sensors allow for the precise heating system control and its economical functioning;

- CFC free insulation of environmentally friendly formula of polyurethane foam of high density and thickness of 75 mm to ensure minimum heat losses;

- casing made from synthetic INOX-coloured wear-proof material.

- LONG LIFE - water tank coated with wear-proof zirconium enamel and two magnesium protectors for an optimal anti-corrosion protection of the whole volume;

- RELIABLE - with a unique protection;

- Combined metallic safety valve;

- Circulation socket;

- Electrical tube heating element, specially designed for this model and manufactured according to the latest innovative technology.

Capacity range:	<b>200</b>
Water tank:	<b>Enameled</b>
Nominal power (kW):	<b>3</b>
Energy efficiency class:	<b>B</b>
Control:	<b>mechanical control</b>
Weight [kg]:	<b>74</b>
Number of coils:	<b>1</b>
Dimensions ØxH [mm]:	<b>600 x 1430</b>
Voltage [V]:	<b>230 V~</b>
Method of water heating:	<b>Electric heating element + one heat exchanger</b>
Pipes diameter (plumbing system / heat exchanger):	<b>3/4" / 3/4"</b>
Nominal pressure [MPa]:	<b>0.8</b>
Heat exchanger surface [m2]:	<b>0.9</b>
Standing loss [W]:	<b>48</b>