







### Technologies:



ENERGY SAVING, RELIABLE, LONG LIFE

- ENERGY SAVING

- With a lower positioned heat exchanger to accumulate to the maximum the energy from the heat source. This model is suitable to connect to solar collectors or heat pumps. The heat exchanger larger area allows that this model of water heaters is universally used;

- Sensor sockets to heat exchanger – the mounted thermal sensors allow for the precise heating system control and its economical functioning;

- Heat insulation from 80 mm thick expanded polyurethane foam to ensure extremely low heat losses and money saved;

- Casing made of a synthetic INOX-coloured wear-proof material.

- LONG LIFE - water tank coated with a wear-proof zirconium enamel and two magnesium protectors for an optimal anti-corrosion protection of the whole volume;

- RELIABLE - with a unique protection;

- Circulation socket;

- Thermometer;

- Electrical tube heating element, specially designed for this model and manufactured according to the latest innovative technology.

Capacity range:	<b>750</b>
Water tank:	<b>Enameled</b>
Control:	<b>mechanical control</b>
Number of coils:	<b>1</b>
Dimensions ØxH [mm]:	<b>1100 x 1675</b>
Voltage [V]:	<b>400V 3N~</b>
Method of water heating:	<b>Electric heating element + one heat exchanger</b>
Pipes diameter (plumbing system / heat exchanger):	<b>1" / 1"</b>
Nominal pressure [MPa]:	<b>0.6</b>
Heat exchanger surface [m <sup>2</sup> ]:	<b>2.03</b>
Standing loss [W]:	<b>123</b>