






Technologies:



IP24



ENERGY SAVING, RELIABLE, LONG LIFE

- **ENERGY SAVING:**
 - With a specially designed horizontally fitted highly efficient heat exchanger to allow the usage of alternative energy sources;
 - the thick insulation of 33 mm Closed-Cells HFO foam ensures extremely low heat losses and saves money;
- **LONG LIFE** – water tank coated with wear-proof zirconium enamel and two magnesium protectors for an optimal anti-corrosion protection of the whole volume;
- **RELIABLE** – with a reliable "6-level protection"
- External thermostat – for setting the water heating temperature;
- Combined safety valve – jointly acting as balance and non-reverse and differential valve;
- Elliptic flange with a special design - guaranteeing your safety;
- Illuminated switch;
- Electrical tube heating element designed especially for this model and manufactured by a last generation technology.
- A constructive solution for the serpentine venting without difficulties.

Installation:	Horizontal
Capacity range:	120
Water tank:	Enameled
Nominal power (kW):	3
Energy efficiency class:	C
Control:	mechanical control
Weight [kg]:	32
Number of coils:	1
Dimensions ØxH [mm]:	462 x 1170
Voltage [V]:	230 V~
Method of water heating:	Electric heating element + one heat exchanger
Pipes diameter (plumbing system / heat exchanger):	1/2" / 1/2"
MIX 40°C [l]:	297
Nominal pressure [MPa]:	0.7
IP protection:	IP24
Heat exchanger surface [m2]:	0.59
Nominal volume [l]:	
Standing loss [W]:	71
Colors:	White