





Technologies:



IP24



ENERGY SAVING, RELIABLE, LONG LIFE

- ENERGY SAVING:

- With a lower positioned heat exchanger (S) of an enlarged area to accumulate to a maximum the alternative source energy. This model is suitable for connecting to solar collectors or heat pumps. The heat exchange larger area allows for the universal usage of this model of water heaters;

- the thick insulation of 35 mm HFO foam ensures extremely low heat losses and saves money;

- LONG LIFE – water tank coated with wear-proof zirconium enamel and two magnesium protectors for an optimal corrosion protection of the whole volume;
- RELIABLE - with a reliable "6-level protection"
- Heat exchanger sensor socket – a thermal sensor is fitted inside it that sends information to the control system for heating;
- External thermostat – for setting the water heating temperature;
- Temperature indicator – to read the water heating temperature;
- Combined safety valve – jointly acting as balance and non-reverse and differential valve;
- Elliptic flange with a special design - guaranteeing your safety;
- Electrical tube heater designed especially for this model and manufactured by a last generation technology.
- Illuminated switch.

Installation:	Vertical
Capacity range:	150
Water tank:	Enameled
Nominal power (kW):	3
Energy efficiency class:	B
Control:	mechanical control
Number of coils:	1
Dimensions ØxH [mm]:	462 x 1420
Voltage [V]:	230 V~
Method of water heating:	Electric heating element + one heat exchanger
Pipes diameter (plumbing system / heat exchanger):	1/2" / 3/4"
MIX 40°C [l]:	378
Nominal pressure [MPa]:	0.7
IP protection:	IP24
Heat exchanger surface [m2]:	0.89
Nominal volume [l]:	
Standing loss [W]:	54
Colors:	