





### Technologies:



IP24



ENERGY SAVING, RELIABLE, LONG LIFE

- **ENERGY SAVING:**
  - With a specially designed horizontally fitted highly efficient heat exchanger to allow the usage of alternative energy sources;
  - the thick insulation of 33 mm CFC-free polyurethane foam ensures extremely low heat losses and saves money;
- **LONG LIFE** - water tank coated with wear-proof zirconium enamel and two magnesium protectors for an optimal anti-corrosion protection of the whole volume;
- **RELIABLE** - with a reliable "6-level protection"
- External thermostat - for setting the water heating temperature;
- Combined safety valve - jointly acting as balance and non-reverse and differential valve;
- Elliptic flange with a special design - guaranteeing your safety;
- Illuminated switch;
- Electrical tube heating element designed especially for this model and manufactured by a last generation technology.
- A constructive solution for the serpentine venting without difficulties.

Installation:	<b>Horizontal</b>
Capacity range:	<b>80</b>
Water tank:	<b>Enameled</b>
Nominal power (kW):	<b>2</b>
Energy efficiency class:	<b>C</b>
Control:	<b>mechanical control</b>
Weight [kg]:	<b>32</b>
Number of coils:	<b>1</b>
Dimensions ØxH [mm]:	<b>387 x 1125</b>
Voltage [V]:	<b>230 V~</b>
Method of water heating:	<b>Electric heating element + one heat exchanger</b>
Pipes diameter (plumbing system / heat exchanger):	<b>1/2" / 1/2"</b>
Nominal pressure [MPa]:	<b>0.7</b>
IP protection:	<b>IP24</b>
Heat exchanger surface [m2]:	<b>0.36</b>
Nominal volume [l]:	
Standing loss [W]:	<b>62</b>