Water heater 30 L, 1.5 kW

dry tubular heating elements, enameled



Technologies:

Find the perfect balance between price and quality with the ELDOM Style water heater!

• ENERGY-SAVING: We use HFO Closed-Cell thermal insulation with a fine, closed-cell structure. This is an eco-friendly, next-generation polyurethane system offering high energy efficiency. The insulation, over 33 mm thick, ensures minimal heat loss and significant savings! The appliance is without a switch
LONG-LASTING:
- SHIELD technology – the water tank is protected by a zirconium-based enamel, formulated specifically for wear resistance;
- Magnesium anode – provides optimal corrosion protection for the interior of the tank.
• SECURE: Features a unique six-level protection system:
- Reliable circular flange – a patented design ensuring maximum safety in the event of overpressure;
- External capillary thermostat – allows for easy adjustment of the desired water heating temperature;
- Capillary thermal cut-out – reliably prevents the appliance from overheating;
- Combined metal valve with dual protective functions – acts as both a check valve and a safety valve;
- Freeze protection – the thermostat automatically maintains the water temperature above 5°C;
- High moisture protection rating – IP24.
• Tubular electric heating element – designed and manufactured by ELDOMINVEST using state-of-the-art technology.
• ECO mode – a thermostat setting of 60°C, at which the water heater operates most economically. • Antibacterial protection: setting the thermostat to the maximum level eliminates all viruses and bacteria.
Long service life
Dry tubular heating elements offer efficiency comparable to standard immersion heaters. At the same time, because they do not come into direct contact with the water and operate under a lower thermal load, their lifespan is significantly longer.
• Modern temperature indicator – you always know the temperature of the water in your water heater.
• Moisture-resistant switch – for convenience and easy switching off of the unit.
• Illuminated on/off indicator.
• Matte white casing.

Installation:	**Vertical**
Capacity range:	**30**
Water tank:	**Enameled**
Nominal power (kW):	**1.5**
Energy efficiency class:	**C**
Control:	**mechanical control**
Dimensions ØxH [mm]:	**387 x 568**
Voltage [V]:	**230 V~**
IP protection:	**IP24**

Colors:	**White**